

### Rubber Gloves HAN1 T224FLC



#### Description

Heavy Weight 0.70mm (28 ml) Thick, Flocklined, Neoprene over Latex Bi-Colour (blue over yellow), 12 inch (30cm) Length Gauntlet. Chlorination treatment.

#### Physical Prop.

Yellow natural latex with blue Neoprene and cotton flocked lining

#### Mechanical

Abrasion EN Level 2      Cut EN Level 1  
Tear EN Level 1          Puncture EN Level 0

#### B.T.T

“Break Through Time” is defined as the elapsed time between first exposure of the fabric to chemical and the rate of permeation reaching a target value. The target permeation rate for tests according to EN 374-3 is one microgram of chemical passing through each square centimetre of fabric every minute. When measured according to the standard method, the breakthrough time is a value by which the performance of different fabrics can be compared.

#### Standard

EN 388, EN 374 AKL, EN 374, EN 421

#### Size

7, 8, 9, 10

Chemical	Chemicals	B.T.T (Min)	Class
	Methanol (A)	>60	3
	40% Sodium Hydroxide (K)	>120	4
	96% Sulphuric Acid (L)	>30	2
	73% Hydrofluoric Acid	>480	6
	10% Hydrochloric Acid	>480	6
	25% Acetic Acid	>120	4
	37% Formaldehyde	>10	1
	98% Ethanol	>30	2