

# **NORTH** Safety Products Africa

Product Data Sheet – HAND PROTECTION – Seamless & Coated Gloves

## Seamless & Coated HAS1 NINJA FORCE



<b>Description</b>	Light Weight Cut Level 5 Glove	
<b>Physical Properties</b>	13 gauge dyneema/synthetic fibre/fibreglass shell with grey Polyurethane coating providing up to 20 times better cut resistance than Aramid-based spun yarn.	
<b>Uses</b>	Excellent light weight cut-resistance glove that also provides abrasion, tear and puncture resistance. Mechanical operations, motor industry and glass and ceramic industry.	
<b>Mechanical</b>	<b>Abrasion</b> EN Level 4 <b>Tear</b> EN Level 4	<b>Cut</b> EN Level 5 <b>Puncture</b> EN Level 2
<b>Chemical</b>	<b>Acids, Bases &amp; Solvents</b> Not suitable	
<b>Heat &amp; Cold</b>	Not suitable	
<b>Precautions</b>	Not suitable for chemical handling	
<b>Standard</b>	EN 388:2003	
<b>Size</b>	M/L	
<b>Maintenance</b>	Both new and used gloves should be thoroughly inspected before use. Gloves should not be left in contaminated condition and where possible, provided no serious hazard exists, should be cleaned before removal. Gloves can be washed with mild detergent then rinsed and dried before use.	