

Personnel Winches HSL1 GSE070



150 kg - 20m, 30m, 40m, 50m
250 kg - 20m, 30m, 40m

Description	The G-Tripod OHP is a quality tripod which is durable and versatile, for confined space and down hole applications. Setup over the horizontal aperture, the G-Tripod can be used in conjunction with the G-Saver II and or G-Winch. Used with the G-Saver II to protect personnel descending into or leaving a confined space, and with the G-Winch for lowering and raising personnel.
Physical Properties	The tripod has been designed to give a secure and stable anchorage for the G-Range of safety products. There are two anchorage points allowing the use of a secondary back-up fall arrester, or other types of lifting/safety equipment. Accessories are available separately to facilitate this. Manufactured in tubular aluminium for lightness and long term durability. The legs are telescopic and adjustable to accommodate uneven surfaces, and ensure easy transport and storage. Rubber cup feet ensure stability in a wide variety of environments.
Uses	Used with the G-Saver II to protect personnel descending into or leaving a confined space, and with the G-Winch for lowering and raising personnel.
Supply	The G-Tripod can be supplied with brackets to suit the following equipment: 1. The G-Saver II or G-Stop. 2. The G-Winch
Precautions	Safe working load 136kg
Standard	CE mark of approval. Fully tested to BS EN 795.